



### DIAMOND DIESEL Diesel Engine Generating Set

#### Group

Power ( Standby kva / kw )	250 kva 200 kw
Power ( Prime kva / kw )	225 kva 180 kw
Dimension without canopy	1200 x 3100 x 1800
(Width / Length / Height) mm	
Dimension with canopy	1400 x 3600 x 2000
(Width / Length / Height) mm	
Weight without canopy	kg 1950
Weight with canopy	kg 2650

#### Diesel Engine

Brand	DIAMOND DIESEL
Model	10 ZLD
Engine Power ( Standby kw )	kw/hp 200 / 268
Engine Power ( Prime kw )	kw/hp 180 / 241
Revolution per minute	rpm 1500
Cycle	4 stroke
Total displacement	lt 9.78
Number of cylinders	6 single line
Bore x Stroke	mm x mm 126 x 130
Governor Type	Mechanic
Induction of rotation	Turbo intercooler
Injection	Direct injection
Direction of rotation	Anti- clockwise when faced flywheel
Cooling	Water cooled
Electrical System	VCD 24
Fuel consumption ( Full load )	lt/h 39.8
Fuel consumption ( %50 load )	lt/h 19.7
Fuel tank capacity	lt/h 320

### Technical Specification

#### Engine

- Diamond Diesel water cooled heavy duty diesel engine.
- 4 stroke, water cooled 1500 rpm
- 24 Volt DC starter and charge alternator
- Dry type disposable air filter
- Tropical type radiator
- A capacity to cool up to 50 °C
- Natural aspiration or Turbo intercooler direct injection
- Flexible fuel pipes and oil discharging
- Engine jacket water heating

#### Chassis

- Mounted on the steel base chassis
- Fuel tank is located in the chassis
- Mechanical fuel indicator
- Rubber brackets that prevent vibration

#### Control Unit

- DKG 307 Automatic control panel
- Ammeter, Voltmeter, Frequency meter
- Generator active power measurement
- Operation hourmeter
- Engine oil pressure measurement
- Relays
- Emergency stop button
- Remote start operation available
- Ignition switch
- Mains / Generator selector switch

- For Automatic Version*
- 2 pcs. contactor in suitable amperage
- Battery charger
- Automatic / Manual selector switch

- For Manual Version*
- Thermic magnetic switch with 3 pole

#### Alternator

- Complies with VDE 0530, IEC34-1, IEC 60034-1, NEMA MG 1.22 standards
- 4-pole, synchron type, single bearing, brushless, star-connected
- Standard voltage 230/400 volt 50 Hz
- IP23 protection class
- Self-excitation
- Automatic voltage regulator (AVR)
- 300% Short circuit resistance with 10 seconds

#### Sound-proof canopy

- Special design for minimizing acoustic level
- Special type muffler and heat insulation
- Acoustic insulation with rot-proof, moisture-repellent and non-flammable material

#### Alternator

Alternator Type	Brushless, direct - coupled, star - connected self alerting, static voltage regulator
Power ( Stanby kva / kw )	250 kva 200 kw
Power ( Prime kva / kw )	225 kva 180 kw
Output Voltage	V 231 / 400 V
Regulation	± 0,5 %
Frequency	Hz 50
Revolution per minute	rpm 1500 d/d
Short circuit current	%300 ( 10 sec )
Insulation	H
Protection	IP 23
Efficiency	90 %
Overloading	1 for one %110, 2 sec. for %150
Power factor	cos Q = 0,8
Harmonic distortion rate (unloaded)	<% 3

